

INSTALLATION INSTRUCTIONS

Note: Toilet must have a flexible water supply line to install the Aquaus Properly. Prior to installation, place a small towel under your water supply line to catch any drips of water.

- 1 Turn water supply off and flush toilet until toilet tank is empty.
- 2 Unscrew toilet water line nut.
- 3 Connect T-Connector to toilet. Firmly tighten by hand.
- 4 Reconnect the toilet water line to the bottom of the T-Connector. Firmly tighten by hand.
- 5 Verify a black washer is inside each end of the sprayer hose and connect the hose to the valve. Firmly tighten by hand.
- 6 Connect the other end of the hose to the sprayer handle. Firmly tighten by hand. Note: Hose is reversible, either end of hose can be connected to the valve or sprayer
- 7 To hang sprayer on toilet tank, attach tank clip to sprayer holder with provided nut and screw. To mount sprayer holder to wall, use drywall anchor and screw (not provided).

DO NOT USE pipe tape or plumbers putty on the threads. They can cause leaking. The rubber washers included create a water-tight seal. When the nuts are screwed on straight and firmly hand tight, there will be no leaking.

Check For Leaks – After installing the Aquaus make sure the pressure control levers on the sprayer are OFF, then turn the water supply on to check for leaks. If leaking accrues around any of the nuts, turn off water and tighten the leaking nut $\frac{1}{4}$ to $\frac{1}{2}$ turn. Repeat this step until the leaking stops. If leaking continues, unscrew the nut and check the washer to make sure it is seated flat and even in the bottom of the nut and has no defects.

How To Use – Make sure the pressure control levers on the sprayer are OFF and turn the Main Valve **8** lever to the on position. Use thumb controls on the sprayer to adjust water pressure. Always turn Main Valve **8** lever to the OFF position after each use.

Need Help? – PLEASE DON'T RETURN THIS PRODUCT TO THE STORE BEFORE CONTACTING A PRODUCT CONSULTANT.

1-954-946-0070 OR help@rinseworks.com

If you need help, installation assistance, replacement parts or have questions, please call or email one of our Product Consultants.

M-F 10 am to 5 pm EST.

Limited 3-Year Warranty – The Aquaus is guaranteed to be free from defects and problems for 3 years from the date of purchase.

