

INSTALLATION INSTRUCTIONS

See Installation Video At - www.rinseworks.com

NOTE - Toilet must have a flexible water supply line to install the Aquaus properly. **NOTE** - Before installation, place a small towel or shallow pan under your water supply line.

- 1 Turn water supply off and flush toilet until toilet tank is empty.
- 2 Unscrew toilet water line nut.
- 3 Connect T-Connector to toilet. Firmly tighten by hand.
- 3A Before installing T-valve 3, turn valve lever 9 counterclockwise, which may be difficult to turn for the first time.
- 4 Reconnect the toilet water line to the bottom of the T-Connector. Firmly tighten by hand.
- 5 Remove the plastic hose nut covers.
- 6 Verify there is a rubber washer in both hose nuts then screw one hose nut on T- Valve threads 6.
- 7 Connect the other end of the hose to the sprayer handle. Firmly tighten by hand.
- 8 To hang sprayer on toilet tank, use the pre-assembled holder and tank clip. To mount sprayer holder to wall, remove the tank clip from sprayer holder and use a drywall anchor and screw (not provided).

DO NOT USE Pipe Tape or Plumbers' Putty on the Threads - which can cause leaking. The rubber washer in the nuts create a water-tight seal when screwed on straight and firmly hand tight.

CHECK FOR LEAKS – After installing the Aquaus make sure the pressure control levers on the sprayer 10 and T-Valve 9 are off. Then slowly turn on the water valve 1 and check for leaks. If leaking accrues around any of the nuts, turn off water and tighten the leaking nuts $\frac{1}{4}$ to $\frac{1}{2}$ turn. Repeat this step until the leaking stops. If leaking continues, unscrew the nut and check the washer to make sure it is seated flat and even in the bottom of the nut and has no defects.

HOW TO USE – Make sure the pressure control levers on the sprayer are OFF. Then turn on the safety shut-off valve lever 9. Point the sprayer in the toilet and turn the sprayer on. Use the thumb levers on the sprayer to adjust the sprayer pressure. Before using the Bidet spray wand make sure you understand how it works and practice adjusting the spray pressure.

After Using the Spray Wand – Always turn off the safety shut-off valve 9 just incase there was ever a leak in the hose or spray wand.

NEED HELP? – PLEASE DON'T RETURN THIS PRODUCT TO THE STORE BEFORE CONTACTING RINSEWORKS CUSTOMER SERVICE 1-954-946-0070 OR HELP@RINSEWORKS.COM

If you need help - installation assistance, replacement parts or have questions, please call or email one of our Product Consultants. M-F 10 am to 5 pm EST.

Limited 3 to 5 Year Warranty – The Aquaus is guaranteed to be free from defects and problems for 3 years from the date of purchase.

